

## RUST PREVENTATIVES

# Oxi Stop® 330

## Indoor Metal Surface Protection

### Long Term Corrosion Protection

Oxi Stop® 330 is recommended for long term corrosion protection of ferrous metals for indoor storage. An excellent water-displacing product that was developed for dip application, but can be sprayed, brushed or flow-coated. For maximum results, parts should be dried after applying Oxi Stop® 330.

### Light Viscosity, Low Odor

Oxi Stop® 330 is a light viscosity, low odor petroleum based rust preventative which, for best results, should be used at full strength. This product leaves an invisible film after drying that can be removed with a mild alkaline cleaner. It can be diluted with a lightweight solvent like mineral spirits if less protection or lower application cost is desired.

#### Technical Data

physical Form	Clear, amber
odor	Low
specific gravity	.810
maximum solubility	negligible
normal working conc.	full strength
normal working temperatures	ambient

#### Packaging Options

5 gallon pail  
55 gallon drum  
330 gallon tote tanks

#### Other Available TLS Products

Shur Draw® 420  
Heavy-Duty semi synthetic drawing compound

Shur Cool® 5010  
Low-foaming top of the line synthetic coolant for steel, stainless steel and aluminium

ID 240  
Concentrated, industrial-strength liquid cleaner/degreaser.



**T & SPECIALTY**  
Chemicals for Industry

300 AIR PARK ROAD · TUPELO, MISSISSIPPI 38801  
662.842.8143 · FAX: 662.842.8583 · 800.882.5966  
WWW.TLSPECIALTY.COM · SUPPORT@TLSPECIALTY.COM