

RUST PREVENTATIVES

Oxi Stop® 345

Indoor Metal Surface Protection

Protection for Ferrous Metals

Oxi Stop® 345 is a high-activity soluble rust preventative for ferrous metals. Oxi stop® 345 is completely soluble, highly active, fully biodegradable.

Application

- 1) Combination of organic surfactant rust inhibitors and inorganic rust inhibitors provide excellent indoor storage protection
- 2) Non-flammable
- 3) The protective film left on the parts by this product is fully water soluble and easily removed in a cleaning cycle.
- 4) The protective film will not interfere with subsequent machining or finishing operations

Technical Data

physical Form	amber liquid
odor	mild
specific gravity	1.03
flash point	none
biodegradable	yes
normal working concentrations (applications)	see below
normal working temperatures	ambient - 140°f
ph @ normal working conc. (depending on conc. used)	8.7 - 9.5

Applications

Recommended use:
immersion tank - dilute with water 1:10 up to full strength depending on protection needed.

Temperature: ambient - 140°f

Packaging Options

5 gallon pail
55 gallon drum
330 gallon tote tanks

Other Available TLS Products

Shur Draw® 420
Heavy-Duty semi synthetic drawing compound

Shur Cool® 5010
Low-foaming top of the line synthetic coolant for steel, stainless steel and aluminium

ID 240
Concentrated, industrial-strength liquid cleaner/degreaser.



T & SPECIALTY
Chemicals for Industry

300 AIR PARK ROAD · TUPELO, MISSISSIPPI 38801
662.842.8143 · FAX: 662.842.8583 · 800.882.5966
WWW.TLSPECIALTY.COM · SUPPORT@TLSPECIALTY.COM