

RUST PREVENTATIVES

Oxi Stop® 696

Outdoor Metal Surface Protection

Long Term Corrosion Protection

Oxi Stop® 696 is recommended for long term corrosion protection of all ferrous and non-ferrous metals.

Dip, Spray, Brush, or Flow Coat

It is a solvent based product that can be applied by dip, spray, brushed or flow-coated. It leaves a thick, black, waxy film ideal for long term protection.

Resistant to High Humidity & Salt Atmospheres

The residual film is highly resistant to high humidity and salt atmospheres, making Oxi Stop® 696 particularly useful for long-term indoor and outdoor storage applications.

Technical Data

chemical comp.	aliphatic hydrocarbons
appearance	clear, dark amber liquid
odor	bland
specific gravity	0.85
flash point	108°F
maximum solubility	negligible
normal working conc.	full strength
normal working temp.	ambient

Application

Auto Rustproofing to the following specifications:

Mil-C-83933A
Mil-PFR 16173E Grade 4, Class 1

Packaging Options

5 gallon pail
55 gallon drum
330 gallon tote tanks

Other Available TLS Products

Shur Draw® 420
Heavy-Duty semi synthetic drawing compound

Shur Cool® 5010
Low-foaming top of the line synthetic coolant for steel, stainless steel and aluminium

ID 240
Concentrated, industrial-strength liquid cleaner/degreaser.



T & SPECIALTY
Chemicals for Industry

300 AIR PARK ROAD · TUPELO, MISSISSIPPI 38801
662.842.8143 · FAX: 662.842.8583 · 800.882.5966
WWW.TLSPECIALTY.COM · SUPPORT@TLSPECIALTY.COM