

RUST REMOVERS

Technical Data

physical Form	clear to light brown liquid
odor	sweet
specific gravity	1.210
flash point	none
maximum solubility	complete
rinsability	good
biodegradable	yes
normal working conc.	1% - 10% by vol
normal working temp.	160°F - 190°F
ph @ working conc.	3.5 - 4.5

Rust Remover 974

Carbon Steel and Stainless Steel

Corrosion Inhibitor

Rust Remover 974 is a concentrated liquid mono ammonium citrate solution. Used at recommended concentrations, it quickly removes light soils, carbon, and corrosion from carbon steel and stainless steel.

Application

Can be applied by spray, immersion, or wiped.

1. Spray 1-5% by Volume @ 160°-190°F.
2. Immersion 3-10% by Volume @ 160°-190°F.
3. Wipe 3-10% by Volume @ ambient temperature

Packaging Options

5 gallon pail
55 gallon drum
330 gallon tote tanks

Other Available TLS Products

Shur Draw® 420
Heavy-Duty semi synthetic drawing compound

Shur Cool® 5010
Low-foaming top of the line synthetic coolant for steel, stainless steel and aluminium

ID 240
Concentrated, industrial-strength liquid cleaner/degreaser.



T & SPECIALTY
Chemicals for Industry