



## LUBRICANTS

# Shur Lube 1300

## Heavy Duty Machining Oil

### Formulated From Renewable Sources

Shur Lube 1300 is an environmentally friendly lubricating oil formulated from renewable resources. It was designed to replace petroleum and animal oils used in metalworking fluids while providing excellent quality and performance.

### Thermal & Oxidative Stability

Shur Lube 1300 has excellent thermal and oxidative stability and provides excellent lubricity and EP properties.

### Aluminum & Ferrous Metals

Shur Lube 1300 is used as is for grinding, cutting, stamping and drawing of aluminum and ferrous metals.



#### Technical Data

appearance	amber liquid
odor	mild
solubility	insoluble in water
specific gravity	0.93
flash point	325° F

#### Packaging Options

5 gallon pail  
55 gallon drum  
330 gallon tote tanks

#### Other Available TLS Products

Shur Draw® 420  
Heavy-Duty semi-synthetic drawing compound

Shur Cut® 429  
Soluble oil for most cutting and milling operations

Shur Cool® 3830  
Non-foaming full synthetic coolant for grinding, milling, drilling and other metalworking operations

**T & SPECIALTY**  
Chemicals for Industry

300 AIR PARK ROAD · TUPELO, MISSISSIPPI 38801  
662.842.8143 · FAX: 662.842.8583 · 800.882.5966  
WWW.TLSPECIALTY.COM · SUPPORT@TLSPECIALTY.COM