

LUBRICANTS

Shur Lube 3100

Heavy Duty Machining Oil

Excellent Performance

Shur Lube 3150 is a heavy duty oil for cutting, drilling, tapping, and honing. It contains a blend of alubricity additives and polymers to provide excellent cutting and machining performance.

Specially Formulated

Shur Lube 3100 is specially formulated for machining ferrous metals and imparts excellent surface finish properties.

Versatile

This versatile product is also used as a coolant for surface grinding, cutting, drilling and other milling operations including CNC machining operations.

Advantages

Contains no dangerous nitrites, nitrates, PCB's, PTTBA, or phenols. Low odor compared to other sulfur containing lubricants

Technical Data

appearance amber liquid odor mild solubility insoluble in water specific gravity 0..92 flash point 325° F

Packaging Options

5 gallon pail 55 gallon drum 330 gallon tote tanks

Other Available TLS Products

Shur Draw ® 420 Heavy-Duty semi-synthetic drawing compound

Shur Cut ® 429 Soluble oil for most cutting and milling operations

Shur Cool ® 3830 Non-foaming full synthetic coolant for grinding, milling, drilling and other metalworking operations



300 AIR PARK ROAD · TUPELO, MISSISSIPPI 38801
662.842.8143 · FAX: 662.842.8583 · 800.882.5966
www.tlspecialty.com · support@tlspecialty.com