INNOVATIVE SOLUTIONS THROUGH TECHNOLOGY & CHEMISTRY

Sprakleen 32D Heavy-duty, Process Detergent

Perfect for Demanding Jobs

Designed to do the most demanding cleaning jobs in the metal working industries at temperatures as low as 125°F.

Spray Washers & Immersion Tanks

SpraKleen 32D can be used for cleaning metal parts in spray washers and immersion tanks. Its built-in surfactants and cleaning agents penetrate and loosen stubborn oils that are fully swept away in the rinse stage.





Other Available TLS Products

Shur Draw [®] 420 Heavy-Duty semisynthetic drawing compound

ID 240 Industrial strength cleaner/degreaser.

Oxi Stop [®] 2120 A unique blend of wetting agents and corrosion inhibitors designed to give indoor rust protection on ferrous metals.





300 AIR PARK ROAD · TUPELO, MISSISSIPPI 38801 662.842.8143 · FAX: 662.842.8583 · 800.882.5966 www.TLSPECIALTY.COM · SUPPORT@TLSPECIALTY.COM

INNOVATIVE SOLUTIONS THROUGH TECHNOLOGY & CHEMISTRY



Sprakleen 32D Heavy-duty, Process Detergent

Quickly Removes Fabricating Lubricants

Solutions of the highly alkaline liquid quickly remove fabricating soils, drawing and buffing compounds, carbonaceous deposits, grease and soils from steel, stainless steel, and other ferrous metals.

Caked on Soils? No Problem

SpraKleen 32D removes burnt soils and carbon from non-aluminum engine blocks. Also cleans the most grimy locomotive, truck and automotive parts, heads, liners, pistons, and rods in diesel rebuild shops. It performs well in hard water, provides long solution life, and rinses thoroughly.

Application Rates

Engines and machinery:

Concrete Floors:

2% - 5% (for general cleaning) 5% - 10% (degreasing) 1% - 5% with water.

PROCESS CLEANERS

Technical Data

chemical composition

appearance odor specific gravity foaming tendency maximum solubility rinsability biodegradable normal working conc. normal working temp. pH @ working conc.

blends of alkaline salts, phosphates, and surfactants clear, light amber liquid mild 1.360 low complete excellent ves 1 - 10% by vol 125°F - 180°F 12.5 - 13.5

Packaging Options

5 gallon pail 55 gallon drum 330 gallon tote tanks

Other Available TLS Products

Shur Draw® 420 Heavy-Duty semisynthetic drawing compound

ID 240 Industrial strength cleaner/degreaser.

Oxi Stop[®] 2120 A unique blend of wetting agents and corrosion inhibitors designed to give indoor rust protection on ferrous metals.





300 AIR PARK ROAD . TUPELO, MISSISSIPPI 38801 662.842.8143 · FAX: 662.842.8583 · 800.882.5966 www.tlspecialty.com · support@tlspecialty.com