

PROCESS CLEANERS



SpraKleen LT 380

Heavy-duty, Process Detergent

Spray Washers & Immersion Tanks

Low foam SpraKleen LT 380 can be used for cleaning steel, stainless steel, and plastic parts in spray washers. Its built-in surfactants and cleaning agents penetrate and loosen stubborn oils that are fully swept away in the rinse stage.

Perfect for Demanding Jobs

Designed to do the most demanding cleaning jobs in the metal working industries at temperatures as low as 100°F.

Quickly Removes Fabricating Lubricants

Solutions of the highly alkaline liquid quickly remove fabricating soils, drawing and buffing compounds, carbonaceous deposits, grease and soils from steel, stainless steel, and other ferrous metals.

Caked on Soils? No Problem

SpraKleen LT 380 removes burnt soils and carbon from non-aluminum engine blocks. Also cleans the most grimy locomotive, truck and automotive parts, heads, liners, pistons, and rods in diesel rebuild shops. It performs well in hard water, provides long solution life, and rinses thoroughly.

Technical Data

appearance	clear, straw colored liquid
odor	mild
specific gravity	1.155
maximum solubility	complete
rinsability	good
biodegradable	yes
normal working concentrations	1 - 10% by vol
normal working temperatures	ambient - 160°F

Packaging Options

5 gallon pail
55 gallon drum
330 gallon tote tanks or Bulk Delivery

Application

Fill tank with desired amount of water. Add SpraKleen LT380 while agitating. Exact amount of product to be used will depend on amount and type of soil. Consult with your representative for recommendations.

Other Available TLS Products

ID 240
Industrial strength cleaner/degreaser.

Shur Draw® 420
Heavy-Duty semisynthetic drawing compound

Oxi Stop® 2120
A unique blend of wetting agents and corrosion inhibitors designed to give indoor rust protection on ferrous metals.



T & SPECIALTY
Chemicals for Industry

300 AIR PARK ROAD · TUPELO, MISSISSIPPI 38801
662.842.8143 · FAX: 662.842.8583 · 800.882.5966
WWW.TLSPECIALTY.COM · SUPPORT@TLSPECIALTY.COM